

EPC4860A(B)/20-05

System Features

- Cost-effective solution: highly integrated solution including power, lightning protection, equipment chamber and DC power back-up
- Easy maintenance: hot swappable power module and fully front-access maintenance system
- Easy installation: platform, ground and H-mast platform mountings are available
- Sealed design: IP55 protection class protects equipment from water and dust, while maintaining a cool operating environment
- Innovative temperature control system: highly reliable heat exchanger and heater operate with easy maintenance and lower cost to keep electronics from exceeding their optimal temperatures
- Lightning protection at AC, DC and PCU sides
- Advanced battery management improves battery lifetime, especially suitable for ragged mains application
- Easy local and remote monitoring
- Safety: system design complies with EN60950 and IEC60950

Introduction

EPC4860A(B)/20-05 power cabinets have been specifically designed with today's distributed network architecture to provide outdoors equipment with reliable DC power. These cabinets offer a cost-effective solution including power and distribution, lightning protection, equipment chamber and DC power back-up. The sealed cabinet, with its reliable temperature control design, assures reliable system running in demanding outdoor environments. Space is available in cabinet to hold equipment like optical transmission equipments.

Applications

- Outdoor stations of GSM, UMTS, CDMA
- Fiber optic transmission systems
- Digital loop carriers



Cabinet

Item	specification	remark
Protection class	IP55	
Operating temperature	-40℃+45℃ -5℃ +45℃	Plus solar radiation of 1120W/m ² , for EPC4860B/20-05 Plus solar radiation 1120W/m ² , for EPC4860A/20-05
Maximum heat dissipation	500W	
Heater Power	300W×2	Only for EPC4860B/20-05
Safety	CE mark	According to EN60959 and IEC60950
Supervision mode	RS232/484 + dry contact	Three digital input

System Configuration

Model	DC capacity	Rectifiers	Monitor	Battery Capacity
EPC4860A(B)/20-05	48V60A	HRS1150-9000, 2~3 units	PSM-BB, 1 unit	48V100AH, 1 string

Distribution

	EPC4860/20-05	Remark
AC input	63A/1P×1 (MCB)	
AC output	10A/1P×1	Socket, with RCD rated 30mA
Battery	63A×1 (MCB)	
DC output	32A×2 (MCB) 16A×4 (MCB)	LLVD BLVD

Power Specification

	Specification	Remark
Input voltage	90-290V/40-65Hz	Single phase
Output voltage	42-58V	Normal 48V
Rectifier power	1150W	HRS1150-9000
Surge current capability	nominal 25kA (8/20us), max. 60kA 15kA(8/20us)	AC input surge protection DC output surge protection

Mechanical Parameter

Parts	Dimension
Cabinet(excluding floorstand)	1130(H)×600(W)×600(D)mm
Battery chamber	295(H)×470(W)×520(D)mm
Equipment chamber	4U(H)×19inch(W)×400mm(D)
Weight	90kg (excluding rectifiers and batteries)

Battery(option)

Item	Specification	Remark
Configuration per string	48V/100Ah	
Single cell model	12V/100Ah	VRLA battery Design life 12 years
Size:D×W×H(mm)	520×107×263	
Weight	41kg	
Safety	CE/UL mark	

Emerson Network Power.
The global leader in enabling
business-critical continuity.

- AC Power
- Embedded Computing
- Outside Plant
- Racks and Integrated Cabinets
- Connectivity
- Embedded Power
- Power Switching & Controls
- Services
- DC Power
- Monitoring
- Precision Cooling
- Surge Protection

Emerson Network Power Co., Ltd.
No. 1 Kefa Rd., Science & Industry Park
Nanshan District 518057, Shenzhen, China
Phone: +86-755-8601-0808
Fax: +86-755-8601-0909
www.emersonnetworkpower.com.cn
www.emersonpower.com.cn

Emerson Network Power and the Emerson
Network Power logo are trademarks and
service marks of Emerson Electric Co.
©2007 Emerson Electric Co.